<b></b>		Rotary Compressor: Fixed Sp			7
		MODEL DATA - FOR COMPRES	SED AIK		_
1	Manufacturer:	Sullivan Palatek			
	Model Number:	SP20+L150	Date:	8/1/2024	
2	X Air-cooled	Water-cooled	Type:	Screw	
			# of Stages:	1	
3*	Rated Capacity at Full Lo	oad Operating Pressure <sup>a, e</sup>	746.9	acfm <sup>a,e</sup>	
4*	Full Load Operating Pres	h	100	psig <sup>b</sup>	-
5	Maximum Full Flow Ope		100	psig <sup>c</sup>	-
6	Drive Motor Nominal Ra		150	_	-
	Drive Motor Nominal Ef	0		hp	_
7	Fan Motor Nominal Rati	-	95.8	percent	-
8			3.0	hp	_
9	Fan Motor Nominal Effic	-	89.5	percent	_
10*	Total Package Input Pow		27.5	kW <sup>e</sup>	_
11	Total Package Input Power at Rated Capacity and Full Load           Operating Pressure <sup>d</sup>		134.5	$kW^d$	
10*		at Rated Capacity and Full Load Operating			-
12*	Pressure <sup>e</sup>		18.01	kW/100 cfm <sup>e</sup>	
13	Isentropic Efficiency		73.80	Percent	
*For mod	els that are tested in the CAGI	Performance Verification Program, these items are	verified by the third party a	dministrator.	
Consult (	CAGI website for a list of parti	cipants in the third party verification program:	www.cagi.org		
NOTES	ISO 1217, Annex C b. The operating press for this data sheet. c. Maximum pressure a maximum pressure a	harge terminal point of the compressor package in accor ACFM is actual cubic feet per minute at inlet conditions are at which the Capacity (Item 3) and Electrical Consur- utainable at full flow, usually the unload pressure setting ttainable before capacity control begins. May require ad	ption (Item 11) were measured for load/no load control or the ditional power.		
AUI	<ul> <li>e. Tolerance is specifie</li> </ul>	power at other than reported operating points will vary w d in ISO 1217, Annex C, as shown in table below:			
d Air & Gas Institute	NOTE: The terms "	power" and "energy" are synonymous for purposes of thi	s document.	Specific Energy	No Load / 2
		Volume Flow Rate at specified conditions	Volume Flow Rate	Consumption	Pov
ember	$\underline{m^3 / \min}$	ft <sup>3</sup> / min	%	%	%
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/-
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	