



D300PD2KR

DUAL PRESSURE \ DUAL CAPACITY \ TIER 4 FINAL \ KOHLER ENGINE \ PORTABLE COMPRESSOR



300CFM/100PSI 230CFM/150PSI



Dependable by design.™

SPECIFICATIONS

Compressor

Model	D300PD2KR
Rated Delivery @ Rated Pressure	300 CFM @ 100 psi - 230 CFM @ 150 psi 8.5 m ³ /min @ 6.9 bar - 6.5 m ³ /min @ 10.4 bar
Operating Pressure Range	70 psi (4.8 bar) - 180 psi (12 bar)
Estimated Weight, Serviced	2,500 lbs
Dimensions L x W x H (in")	134" x 55" x 72"

Engine

Type	Diesel
Make & Model	KOHLER 2504 Tier 4 Final
Idle Speed	1650 RPM
Fuel Tank Capacity	30 gal (109.8 L)
Horsepower @ rated RPM	74 hp
Full Load Speed	2400 RPM @ 300 CFM 1900 RM @ 230 CFM

FEATURES

- » 130mm Diameter Twin Screw Air End
- » Exclusive Three Year Warranty On Air End
- » Automatic 0 to 100% Capacity Control
- » Two Stage Dry Type Air Filter with Safety Elements - External Access
- » Multiple Service Connections
- » Oil Level Sight Gauge
- » Side by Side Coolers for Compressor and Engine
- » KOHLER 2504 Tier 4 Engine
- » Steel Fuel Tank
- » Cooler Access Panel for Cleaning
- » Safety Chains
- » 15" Wheels & Radial Tires
- » Choice of Lunnette Eye or Ball Hitch on Height Adjustable Drawbar
- » Large Tool Boxes in Each Side with Lockable Handles
- » Galvanneal Enclosure
- » Galvanized Wheel Wells and Internal Panels
- » Easily Removable Upper Enclosure
- » Automatic Shutdown and Protection System
- » Automatic Blowdown Valve
- » Stop, Turn and Tail Lights
- » Unloaded Starting
- » High-Low Selector Valve
- » Spin on oil filter/separator

CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC)

- Digital Readouts:
- » Compressor temperature
 - » Discharge pressure
 - » Engine oil pressure
 - » Engine Coolant temperature
 - » Voltmeter
 - » Tachometer
 - » Fuel level - low fuel warning and shutdown
 - » Fault Codes
 - » Unit converter
 - » Multilingual capabilities
 - » Waterproof up to six feet



Sullivan-Palatek, Inc.

1201 West US Highway 20
Michigan City, IN 46360

219.874.2497

sullivan-palatek.com

info@palatek.com