		Rotary Compressor: Fixed Sp MODEL DATA - FOR COMPRES			7
					_
1	Manufacturer:	Sullivan Palatek			
	Model Number: SP25-200		Date:	8/23/2024	
2	X Air-cooled	Water-cooled	Type:	Screw	
			# of Stages:	1	
3*	Rated Capacity at Full Load Operating Pressure ^{a, e}		933.8	acfm ^{a,e}	-
		1			-
4*			125	psig ^b	
5	5 Maximum Full Flow Operating Pressure ^c		125	psig ^c	
6	Drive Motor Nominal Ra	ting	200	hp	
7	Drive Motor Nominal Eff	iciency	96.2	percent	
8	Fan Motor Nominal Ratin	ng (if applicable)		•	-
	Ean Motor Nominal Efficiency		3.0	hp	-
9			89.5	percent	_
10*	Total Package Input Power at Zero Flow ^e		57.6	kW ^e	
11	Total Package Input Pow	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d		kW^d	
		t Rated Capacity and Full Load Operating	180.6		-
12*	12* e Pressure		19.34	kW/100 cfm ^e	
				_	-
13 Isentropic Efficiency			77.68	Percent	
		Performance Verification Program, these items are		lministrator.	
		cipants in the third party verification program:	www.cagi.org		
NOTES	ISO 1217, Annex C;	harge terminal point of the compressor package in accord ACFM is actual cubic feet per minute at inlet conditions			
	b. The operating pressu for this data sheet.	re at which the Capacity (Item 3) and Electrical Consum	ption (Item 11) were measured		
		ttainable at full flow, usually the unload pressure setting			
	d. Total package input	ttainable before capacity control begins. May require ad power at other than reported operating points will vary w			
		d in ISO 1217, Annex C, as shown in table below:			
Air & Gas Institut	NOTE: The terms	power" and "energy" are synonymous for purposes of thi Volume Flow Rate	s document.	Specific Energy	No Load /
		at specified conditions	Volume Flow Rate	Consumption	Po
mber	<u>m³ / min</u>	<u>ft³ / min</u>	%	%	(
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/-
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	17-