		Rotary Compressor: Fixed Sp MODEL DATA FOR COMPRES			
	T	MODEL DATA - FOR COMPRES	SED AIK		
1	Manufacturer:	Sullivan Palatek			
	Model Number:	SP25-HH350	Date:	11/6/2024	
2	X Air-cooled Water-cooled		Type:	Screw	
			# of Stages:	1	
3*	Rated Capacity at Full Lo	ad Operating Pressure ^{a, e}	1115.8	acfm ^{a,e}	
4*	Full Load Operating Pres	sure	175	psig ^b	
5	Maximum Full Flow Ope		175	psig ^c	
	Drive Motor Nominal Ra				
6	Drive Motor Nominal Eff	0	350	hp	
7		-	96.2	percent	
8	Fan Motor Nominal Rati		7.5	hp	
9	Fan Motor Nominal Effic	-	91.0	percent	
10*	Total Package Input Pow	er at Zero Flow ^e	80.3	kW ^e	
11	Total Package Input Pow Operating Pressure ^d	er at Rated Capacity and Full Load	267.5	kW^d	
12*	Package Specific Power a Pressure ^e	t Rated Capacity and Full Load Operating	23.98	kW/100 cfm ^e	
13	Isentropic Efficiency		74.68	Percent	
		Performance Verification Program, these items are		dministrator.	
NOTES	 a. Measured at the disc ISO 1217, Annex C; b. The operating pressu for this data sheet. c. Maximum pressure a maximum pressure a d. Total package input 	cipants in the third party verification program: harge terminal point of the compressor package in accorr ACFM is actual cubic feet per minute at inlet conditions re at which the Capacity (Item 3) and Electrical Consum ttainable at full flow, usually the unload pressure setting tainable before capacity control begins. May require ad power at other than reported operating points will vary w d in ISO 1217, Annex C, as shown in table below:	ption (Item 11) were measured for load/no load control or the ditional power.		
d Air & Gas Institute		power" and "energy" are synonymous for purposes of this	s document.		
		Volume Flow Rate at specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / 2 Pov
ember	$\underline{m^3} / \underline{min}$	ft ³ / min	%	%	%
	Below 0.5	Below 17.6	+/- 7	+/- 8	
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/-
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	