



D300PD2KR

DUAL PRESSURE \ DUAL CAPACITY \ TIER 4 FINAL \ KOHLER ENGINE \ PORTABLE COMPRESSOR



300CFM/100PSI 230CFM/150PSI



Dependable by design.[™]

SPECIFICATIONS

Compressor

Model	D300PD2KR
Rated Delivery @ Rated Pressure	300 CFM @ 100 psi - 230 CFM @ 150 psi 8.5 m3/min @ 6.9 bar - 6.5 m3/min @ 10.4 bar
Operating Pressure Range	70 psi (4.8 bar) - 180 psi (12 bar)
Estimated Weight, Serviced	2,500 lbs
Dimensions L x W x H (in")	134" x 55" x 72"

Engine

Туре	Diesel
Make & Model	KOHLER 2504 Tier 4 Final
Idle Speed	1650 RPM
Fuel Tank Capacity	30 gal (109.8 L)
Horsepower @ rated RPM	74 hp
Full Load Speed	2400 RPM @ 300 CFM 1900 RM @ 230 CFM



FEATURES

- » 130mm Diameter Twin Screw Air End
- » Exclusive Three Year Warranty On Air End
- Automatic 0 to 100% Capacity Control
- Two Stage Dry Type Air Filter with Safety Elements - External Access
- **Multiple Service Connections**
- Oil Level Sight Gauge
- Side by Side Coolers for Compressor and Engine KOHLER 2504 Tier 4 Engine
- » » Steel Fuel Tank
- Cooler Access Panel for » Cleaning
- » Safety Chains
- » 15" Wheels & Radial Tires
- » Choice of Lunnette Eye or Ball Hitch on Height Adjustable Drawbar
- » Large Tool Boxes in Each Side with Lockable Handles
- » Galvanneal Enclosure
- » Galvanized Wheel Wells and **Internal Panels**
- » Easily Removable Upper Enclosure
- » Automatic Shutdown and Protection System
- » Automatic Blowdown Valve
- » Stop, Turn and Tail Lights
- » Unloaded Starting
- » High-Low Selector Valve
- » Spin on oil filter/separator

.CONTROLLER

Sullivan-Palatek Electronic Controller (SPEC) **Digital Readouts:**

- » Compressor temperature
- » Discharge pressure
- » Engine oil pressure
- » Engine Coolant temperature
- » Voltmeter
- » Tachometer
- » Fuel level low fuel warning and shutdown
- » Fault Codes
- » Unit converter
- » Multilingual capabilities
- » Waterproof up to six feet

Sullivan-Palatek, Inc.

219.874.2497

🛞 sullivan-palatek.com 🛛 😤 info@palatek.com